



You are a Resource Revolutionary.

Crossing boundaries

TOMRA 3C

Everything you expect from conventional sorting... and more

As a technology leader, TOMRA continues to be a pioneer in sensor-based sorting in the food, recycling, mining and other industries.

TOMRA's food sorters are not only the most efficient solution to sort your product, they are also a smart way to invest in your food business.

If you are interested in a free demonstration with your own product or if you need more information, please contact us directly.



TOMRA Food EMEA

Research Park Haasrode 1622
Romeinse straat, 20
3001 Leuven
BELGIUM

Tel: +32 16 396 396
Fax: +32 16 396 390
food@tomra.com
www.tomra.com/food

TOMRA Food AMERICAS

875 Embarcadero Drive
West Sacramento
California 95605
U.S.A.

Tel: +1 916 388 3900
Fax: +1 916 388 3901
food.us@tomra.com
www.tomra.com/food

TOMRA Food APAC

Unit 1, 20 Anella Ave,
Castle Hill, 2154
NSW
AUSTRALIA

Tel: +61 2 8624 0100
Fax: +61 2 8624 0101
food.asia@tomra.com
www.tomra.com/food

TOMRA Food CHINA

1A/E, Rihua Building, No.8,
Xinfeng 2nd Road, Huli District,
Xiamen, Fujian, 361006
P.R.CHINA

Tel: +86 592 572 0780
Fax: +86 592 572 0779
food.china@tomra.com
www.tomra.com/food






TOMRA 3C

OPTICAL SORTER




After years of global teamwork, laser technology is introduced to the market of conventional sorting with the **TOMRA 3C**. Addressing your daily challenges in seeds, grains, beans, pulses and nuts sorting, the sorter's optimal and reliable performance ensures your products meet the highest standard for food safety and quality. Every element is designed to increase the machine's ease of use, leading the way in user experience.



SUPERIOR GLASS AND FOREIGN MATERIAL REMOVAL
Dual laser induced scattering



REMOVING SUBTLEST COLOR AND SHAPE DEFECTS
Double-sided RGB cameras combined with high intensity, focused LED lighting




OPTIMAL PERFORMANCE GUARANTEED
Intelligent auto cleaning



MINIMAL BREAKAGE AND FAST MAINTENANCE
Soft landing chute with tool-free removal



OPTIMAL EFFICIENCY AND INTUITIVE TUNING
Application specific tuning parameters with award-winning GUI, TOMRA ACT



MINIMIZED DOWNTIME
Remote and on-screen alerts








LOW FALSE REJECTION
High speed valve with direct nozzle connection

WORKING PRINCIPLE

The produce falls from the hopper onto the shaker pan, spreading evenly on the infeed chute. Dual laser and double-sided cameras inspect the produce on both sides. A few milliseconds later, the intelligent ejection system rejects all defects. The good product continues its way via the accept chute, while the defects are diverted via the reject chute.

DIMENSIONS AND SPECIFICATIONS*



CAPACITY (T/h*)

1.2 - 1.8

2.4 - 3.6

3.6 - 5.4

4.8 - 7.2

POWER (kVA)

0.4

0.7

1.1

1.4

AIR (m³/h)

< 190

< 380

< 560

< 760

*The max. flow rate depending on product type, IDL and the application of a single or dual-sort arrangement, with single or double reject recycling



SUNFLOWER SEEDS



PUMPKIN SEEDS



WATERMELON SEEDS

